MasterJib

MovieTech

Scope of delivery:	▪ crane support with integrated base segment, horizontal and double vertical brake, adapter for monitor support, pan angle display, water level
	▪ end segment 500mm (alternatively 1000mm)
	▪ counter weight support incl. steel counter weight rods (Ø 30mm)
	▪ arm segments 500/1000 mm with quick release system (number depends on version)
	▪ panning handle flexible to mount
	▪ crane head with mitchell base plate and handles on the side, horizontal angle adjustable
weights:	▪ segment 500mm: 4,95kg, 1000mm: 8,3kg
	▪ crane support incl. base segment: 25,3kg
	▪ counter weight holder: 15,2kg
	▪ crane head: 14,95kg
	▪ panning handles: 1kg each
	▪ total weight in version R6: 83,95kg
segment dimensions:	120x150x500/1000mm
payload:	50kg in version R6
accessories:	crane dolly CD5/ 6 remote head P15
	ball adapter euromount adapter
	counterweights transport case with rolls
	display support

(Delivery without remote head and crane dolly)

- *high payload but small space ratio*
- *no additional bracing, quick assembling*
- *available and mountable in different length versions*
- *compatible for remote and fluid heads as well as 3D Rigs*

MasterJib

MovieTech

The MasterJib is available in 6 different length versions. Even in confined space conditions you thus may use this powerful equipment in its shortest version. With minimal shadowing it's also perfect for working in studios.

The steel counterweight rods (Ø 30mm outside) may carry different types of counterweights such as stage weights and fitness weights.

Due to integrated horizontal and vertical brakes it's easy to realize precise panning shots or still photographs with the MasterJib. Via a crane column the jib can be mounted on every MovieTech crane dolly.

The panning handles help to operate the jib. They may be mounted flexibly where needed.

MasterJib

MovieTech

MovieTech Master-Jib   Overview on the versions R1-R6 (A)

Vers. R1
1130 mm
770 mm
500 | 360 | 360

Vers. R3
2130 mm
500 | 360 | 360 | 1000

Vers. R5
3130 mm
500 | 360 | 360 | 1000 | 1000

Vers. R6 (A)
3630 mm
1000 | 360 | 360 | 1000 | 1000 | 500

Side view of version R6
~4.44m
~1.43m
~1m